

HII 64500 FT



Future-oriented technologies from Beko

Beko invests in research and development so that you can deal with everyday life with ease. To this end, we research the use of the kitchen in the every day life and bring you the most practical and functional ideas home. Individually adapted to your ideas and requirements, we put them into practice. Your satisfaction is our motivation.



Booster function

The booster function activates all heating elements for a quick reaching of the set baking temperature.



Induction cooker

The latest and most efficient cooking technology: Induction cookers are only heated when a pot is placed on the stove. And also only where he stands. This automatically detects the magnetic field. Beneath the glass field is a coil that generates a magnetic field. If a pot is placed on the cooking zone, the heat is generated directly in the cookware. This saves energy and conserves resources. Burnt fingers are a thing of the past.



beko Doko Doko

Slide Touch sensor buttons

The new SlideTouch sensors are in the trend: by tapping directly or by moving along the operating scale, the individual cooking zones are controlled precisely. There are 19 cooking stages for each cooking zone. The selected cooking level is shown in the display. Especially useful is the Stop & Go button for short interruptions. This means you are always on the safe side. The cooking time can be set with the timer: the cooking zone switches off automatically and the cooking time is signaled.



HII 64500 FT

General Features

Type: Induction cooker Number of cooking zones: 4

Color: Black



Front left

180 mm - 1800 W / 2500 W (booster)

Rear left

180 mm - 1800 W / 2500 W (booster)

Front right

145 mm - 1400 W / 1800 W (booster)

Rear right

210 mm - 2200 W / 3200 W (booster)

Functions

Overflow protection

Child safety

Booster function - fast heating

Connection cable

residual heat indicator

Cooking field

Frameless

Operation indicator

Memory function

Digital display of the cooking level

timer

Safety shutdown (against long-running operation)

Control: Slide Touch Sensor buttons



Technical specifications

Frequency: 50(Hz) Voltage: 220-415 V Current: 2 x 16A/32A

Power consumption: 7200(W)

Cable length: 2m

External Dimensions

Height: 5.5(cm) Width: 58(cm) Depth: 51.0(cm)

Installation Dimensions

56 x 49cm